

# Earthborn Eggshell No.17

**Earthborn Eggshell No.17** is a durable, washable and scuff resistant environmentally friendly paint suitable for interior woodwork. It has a silk finish and a unique formulation that is totally oil and acrylic free, containing virtually no VOCs.

## 1. Coverage

Approximately 14m<sup>2</sup> per litre

## 2. Thinner

Water (up to 10%)

## 3. Drying times

The product is touch-dry in 1-2 hours. Allow 6-12 hours between coats. Due to the rapid drying rate of Earthborn Eggshell, care needs to be taken to work in a logical manner so as not to 'over-brush' or 'lay off' areas already painted. Particular care needs to be taken when painting large flat areas or panels.

## 4. Uses

Earthborn Eggshell No.17 is suitable for use on interior wood – doors, window frames, furniture, shelving, skirting boards and other smooth planed wood.

N.B. Earthborn Eggshell No.17 is not recommended for floors or other heavy-duty surfaces.

## 5. Preparation

For best results do not apply in temperatures below 8°C. Wood surfaces should be prepared with Earthborn Multi Purpose Primer and lightly sanded prior to application. Previously painted surfaces should be sanded to provide a key, and then prime with Earthborn Multi Purpose Primer. Loose or flaking material must be removed with a brush or scraper. Defective wood should be repaired, exuding resin removed and knots treated with a proprietary knotting solution.

## 6. Application

Stir thoroughly before use. For best results apply two coats of undiluted Eggshell No.17. Give a light sanding between coats.

Earthborn Eggshell No.17 can be applied by brush, roller or spray gun.

## 7. Cleaning

Remove as much Earthborn Eggshell No.17 as possible from tools before cleaning with warm, soapy water. To minimise water usage please avoid cleaning under running water.

## 8. Storage

Keep containers tightly sealed in a cool, dry and frost-free place. Unopened containers have a minimum shelf life of 12 months when stored under the recommended conditions.

## 9. Ingredients

Water, Binder (VAE / Polyurethane emulsions), Pigments (Inc. Titanium Dioxide), Fillers (China Clay / Dolomite), Anionic / Non-ionic surfactant, Thickeners (Urethane / Cellulose derivative), Acidity regulator (Sodium Hydroxide), Defoamer (VOC free mineral oil), Preservatives ((1, 2-benzisothiazol-3(2H)-one and 2-methyl-2H-isothiazol-3-one)

## 10. Safety

Please refer to Material Safety Data Sheet

## 11. Disposal

Any leftover paint should not be emptied into drains or watercourses but allowed to dry and reference made to local authority disposal guidelines.

## 12. VOC content

This products has a VOC content of less than 0.5g/L

## 13. Moisture Vapour Transmission

MVT value = 227.5 g/m<sup>2</sup> per 24 hours.

## 14. Safety of Toys Standard (EN71-3:1995)

*The user is recommended to test the product on the intended surface to ensure its suitability.*

*Our colours are made using a traditional batch process so there may be slight colour variations between batches and the colour chart. Whilst every precaution is taken to ensure colour continuity, please make sure you have sufficient paint from the same batch to complete your work.*

Earthborn  
Frodsham Business Centre  
Bridge Lane  
Frodsham  
Cheshire WA6 7FZ

Tel: 01928 734171 [www.earthbornpaints.co.uk](http://www.earthbornpaints.co.uk)